

CP-3000 and SP-3000 Calibration Chart

Height (in.)	Volume (Gal)						
81.5	3,861.19	70.5	3,340.05	59.25	2,807.06	48	2,274.08
81.25	3,849.35	70.25	3,328.21	59	2,795.22	47.75	2,262.23
81	3,837.51	70	3,316.36	58.75	2,783.38	47.5	2,250.39
80.75	3,825.66	69.75	3,304.52	58.5	2,771.53	47.25	2,238.55
80.5	3,813.82	69.5	3,292.68	58.25	2,759.69	47	2,226.70
80.25	3,801.97	69.25	3,280.83	58	2,747.84	46.75	2,214.86
80	3,790.13	69	3,268.99	57.75	2,736.00	46.5	2,203.01
79.75	3,778.29	68.75	3,257.14	57.5	2,724.16	46.25	2,191.17
79.5	3,766.44	68.5	3,245.30	57.25	2,712.31	46	2,179.32
79.25	3,754.60	68.25	3,233.45	57	2,700.47	45.75	2,167.48
79	3,742.75	68	3,221.61	56.75	2,688.62	45.5	2,155.64
78.75	3,730.91	67.75	3,209.77	56.5	2,676.78	45.25	2,143.79
78.5	3,719.06	67.5	3,197.92	56.25	2,664.94	45	2,131.95
78.25	3,707.22	67.25	3,186.08	56	2,653.09	44.75	2,120.10
78	3,695.38	67	3,174.23	55.75	2,641.25	44.5	2,108.26
77.75	3,683.53	66.75	3,162.39	55.5	2,629.40	44.25	2,096.42
77.5	3,671.69	66.5	3,150.55	55.25	2,617.56	44	2,084.57
77.25	3,659.84	66.25	3,138.70	55	2,605.71	43.75	2,072.73
77	3,648.00	66	3,126.86	54.75	2,593.87	43.5	2,060.88
76.75	3,636.16	65.75	3,115.01	54.5	2,582.03	43.25	2,049.04
76.5	3,624.31	65.5	3,103.17	54.25	2,570.18	43	2,037.19
76.25	3,612.47	65.25	3,091.32	54	2,558.34	42.75	2,025.35
76	3,600.62	65	3,079.48	53.75	2,546.49	42.5	2,013.51
75.75	3,588.78	64.75	3,067.64	53.5	2,534.65	42.25	2,001.66
75.5	3,576.94	64.5	3,055.79	53.25	2,522.81	42	1,989.82
75.25	3,565.09	64.25	3,043.95	53	2,510.96	41.75	1,977.97
75	3,553.25	64	3,032.10	52.75	2,499.12	41.5	1,966.13
74.75	3,541.40	63.75	3,020.26	52.5	2,487.27	41.25	1,954.29
74.5	3,529.56	63.5	3,008.42	52.25	2,475.43	41	1,942.44
74.25	3,517.71	63.25	2,996.57	52	2,463.58	40.75	1,930.60
74	3,505.87	63	2,984.73	51.75	2,451.74	40.5	1,918.75
73.75	3,494.03	62.75	2,972.88	51.5	2,439.90	40.25	1,906.91
73.5	3,482.18	62.5	2,961.04	51.25	2,428.05	40	1,895.06
73.25	3,470.34	62.25	2,949.19	51	2,416.21	39.75	1,883.22
73	3,458.49	62	2,937.35	50.75	2,404.36	39.5	1,871.38
72.75	3,446.65	61.75	2,925.51	50.5	2,392.52	39.25	1,859.53
72.5	3,434.81	61.5	2,913.66	50.25	2,380.68	39	1,847.69
72.25	3,422.96	61.25	2,901.82	50	2,368.83	38.75	1,835.84
72	3,411.12	61	2,889.97	49.75	2,356.99	38.5	1,824.00
71.75	3,399.27	60.75	2,878.13	49.5	2,345.14	38.25	1,812.16
71.5	3,387.43	60.5	2,866.29	49.25	2,333.30	38	1,800.31
71.25	3,375.58	60.25	2,854.44	49	2,321.45	37.75	1,788.47
71	3,363.74	60	2,842.60	48.75	2,309.61	37.5	1,776.62
70.75	3,351.90	59.75	2,830.75	48.5	2,297.77	37.25	1,764.78
		59.5	2,818.91	48.25	2,285.92	37	1,752.94

CP-3000 and SP-3000 Calibration Chart

36.75	1,741.09	25.5	1,208.10	14.25	675.12	3	142.13
36.5	1,729.25	25.25	1,196.26	14	663.27	2.75	130.29
36.25	1,717.40	25	1,184.42	13.75	651.43	2.5	118.44
36	1,705.56	24.75	1,172.57	13.5	639.58	2.25	106.60
35.75	1,693.71	24.5	1,160.73	13.25	627.74	2	94.75
35.5	1,681.87	24.25	1,148.88	13	615.90	1.75	82.91
35.25	1,670.03	24	1,137.04	12.75	604.05	1.5	71.06
35	1,658.18	23.75	1,125.19	12.5	592.21	1.25	59.22
34.75	1,646.34	23.5	1,113.35	12.25	580.36	1	47.38
34.5	1,634.49	23.25	1,101.51	12	568.52	0.75	35.53
34.25	1,622.65	23	1,089.66	11.75	556.68	0.5	23.69
34	1,610.81	22.75	1,077.82	11.5	544.83	0.25	11.84
33.75	1,598.96	22.5	1,065.97	11.25	532.99	0	0.00
33.5	1,587.12	22.25	1,054.13	11	521.14		
33.25	1,575.27	22	1,042.29	10.75	509.30		
33	1,563.43	21.75	1,030.44	10.5	497.45		
32.75	1,551.58	21.5	1,018.60	10.25	485.61		
32.5	1,539.74	21.25	1,006.75	10	473.77		
32.25	1,527.90	21	994.91	9.75	461.92		
32	1,516.05	20.75	983.06	9.5	450.08		
31.75	1,504.21	20.5	971.22	9.25	438.23		
31.5	1,492.36	20.25	959.38	9	426.39		
31.25	1,480.52	20	947.53	8.75	414.55		
31	1,468.68	19.75	935.69	8.5	402.70		
30.75	1,456.83	19.5	923.84	8.25	390.86		
30.5	1,444.99	19.25	912.00	8	379.01		
30.25	1,433.14	19	900.16	7.75	367.17		
30	1,421.30	18.75	888.31	7.5	355.32		
29.75	1,409.45	18.5	876.47	7.25	343.48		
29.5	1,397.61	18.25	864.62	7	331.64		
29.25	1,385.77	18	852.78	6.75	319.79		
29	1,373.92	17.75	840.94	6.5	307.95		
28.75	1,362.08	17.5	829.09	6.25	296.10		
28.5	1,350.23	17.25	817.25	6	284.26		
28.25	1,338.39	17	805.40	5.75	272.42		
28	1,326.55	16.75	793.56	5.5	260.57		
27.75	1,314.70	16.5	781.71	5.25	248.73		
27.5	1,302.86	16.25	769.87	5	236.88		
27.25	1,291.01	16	758.03	4.75	225.04		
27	1,279.17	15.75	746.18	4.5	213.19		
26.75	1,267.32	15.5	734.34	4.25	201.35		
26.5	1,255.48	15.25	722.49	4	189.51		
26.25	1,243.64	15	710.65	3.75	177.66		
26	1,231.79	14.75	698.81	3.5	165.82		
25.75	1,219.95	14.5	686.96	3.25	153.97		